



SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	pH Solution Wide Range
Other means of identification	Not available
Recommended use	Water Testing Solution
Recommended restrictions	None known.
Manufacturer information	Pro Products LLC 7201 Engle Road Fort Wayne, IN 46804-5875 US Phone: 260-483-2519 Emergency Phone: 1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 1
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause cancer.

Precautionary statement

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid breathing mist or vapor. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

Response

In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	30-60*
Methanol		67-56-1	1-5*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention immediately.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Keep away from sources of ignition. No smoking. Avoid contact with eyes and skin. Wear rubber gloves and safety glasses with side shields. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Dry chemical. Alcohol foam. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only with adequate ventilation.

Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use personal protective equipment as required. When using, do not eat, drink or smoke. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a closed container away from incompatible materials. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store in cool place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers. Keep out of reach of children.

Do not store at temperatures above 120°F (49°C).

Store away from heat, flames, sparks, and all other sources of ignition.

8. Exposure Controls/Personal Protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Methanol (CAS 67-56-1)	STEL	328 mg/m3
		250 ppm
	TWA	262 mg/m3
		200 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m3 250 ppm
	TWA	260 mg/m3
		200 ppm

Biological limit values

ACGIH Biological Exposure Indices		Determinant	Specimen	Sampling Time
Components	Value			
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Eye wash facilities and emergency shower must be available when handling this product. Provide eyewash station. Use only under good ventilation conditions or with respiratory protection.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Impervious gloves. Confirm with reputable supplier first.

Other	Wear appropriate chemical resistant clothing. As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid
Color	Dark green
Odor	Alcohol
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	173.3 °F (78.5 °C)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	73.4 °F (23.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	> 3.3 (ethanol)
Flammability limit - upper (%)	< 19 (ethanol)
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	48 mmHg @ 20°C for SDA (3A) Ethyl Alcohol
Vapor density	1.6 (Air=1) @ 20°C for SDA (3A) Ethyl Alcohol
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents. Nitric acid..
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid temperatures exceeding the flash point. Heat, open flames, static discharge, sparks and other ignition sources.
Incompatible materials	Acids. Caustics. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Skin absorption, Inhalation, Ingestion.
---------------------------	--

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful. May cause damage to organs by inhalation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause irritation to the respiratory system.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
Ethanol (CAS 64-17-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 15800 mg/kg, SIDS initial assessment report
<i>Inhalation</i>		
LC50	Cat	85.4 mg/L, 4.5 Hours, ECHA 43.7 mg/L, 6 Hours, ECHA
	Mouse	> 60000 ppm, 60 Minutes, ECHA 79.4 mg/L, 134 Minutes, ECHA
	Rat	> 115.9 mg/L, 4 Hours, ECHA 31623 ppm, 4 Hours, HMIRA 20000 ppm, 10 Hours, HSDB 51.3 mg/L, 6 Hours, ECHA
<i>Oral</i>		
LD50	Dog	5.5 g/kg, HSDB
	Guinea pig	5600 mg/kg, HSDB
	Monkey	6000 mg/kg
	Mouse	10500 ml/kg, ECHA 3450 mg/kg, SAX
	Pig	> 5000 mg/kg, ECHA
	Rat	1187 - 2769 mg/kg, ECHA 12400 mg/kg, ECHA 10470 mg/kg, ECHA 7800 ml/kg, ECHA
Methanol (CAS 67-56-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15800 - 20000 mg/kg, SIDS report/HSDB
	Rat	> 450000 mg/kg, SIDS report/HSDB
<i>Inhalation</i>		
LC50	Cat	85.4 mg/l/4h, HSDB 85.4 mg/L, 4.5 Hours, ECHA/HSDB 43.7 mg/L, 6 Hours, ECHA
	Mouse	79.4 mg/L, 134 Minutes, ECHA
	Rat	> 115.9 mg/L, 4 Hours, ECHA 64000 ppm, 4 Hours, HSDB 130.7 mg/L, 4 Hours, ECHA 128.2 mg/L, 4 Hours, ECHA

Components	Species	Test Results
		92.6 mg/L, 6 Hours, ECHA
		87.5 mg/L, 6 Hours, ECHA
		83.2 - 128.8 mg/l/4h, SIDS report/HSDB
		82.1 mg/L, 6 Hours, ECHA
<i>Oral</i> LD50	Dog	8000 mg/kg, HSDB
	Human	143 - 300 mg/kg, HSNO CCID/Sigma-Aldrich
	Monkey	7000 - 9000 mg/kg, ECHA
		6000 mg/kg, ECHA
		3000 mg/kg, RTECS
		2000 mg/kg, HSDB
	Mouse	7300 mg/kg, HSDB
	Pig	> 5000 mg/kg, ECHA
	Rabbit	14200 - 14400 mg/kg, RTECS
		14.4 g/kg, HSDB
	Rat	1187 - 2769 mg/kg
		790 - 13000 mg/kg, SIDS report/HSDB
		5628 mg/kg, HSDB
Skin corrosion/irritation	Not available.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Potassium hydroxide (CAS 1310-58-3)		Irritant
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.	
Carcinogenicity	May cause cancer.	
Canada - Manitoba OELs: carcinogenicity		
ETHANOL (CAS 64-17-5)		Confirmed animal carcinogen with unknown relevance to humans.
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethanol (CAS 64-17-5)		Volume 44, Volume 96, Volume 100E Volume 96, Volume 100E
US - California Proposition 65 - CRT: Listed date/Carcinogenic substance		
Phenolphthalein (CAS 77-09-8)		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	May damage fertility or the unborn child.	
Teratogenicity	Methanol has produced teratogenic effects in mice exposed by inhalation to high concentrations that did not produce significant maternal toxicity.	
Specific target organ toxicity - single exposure	Respiratory tract irritation. Narcotic effects.	

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components		Species	Test Results	
Ethanol (CAS 64-17-5)	Crustacea	EC50	Daphnia	11744.5 mg/L, 48 Hours
	Aquatic			
	Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/L, 48 hours
	Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/L, 96 hours
Methanol (CAS 67-56-1)	Aquatic			
	Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/L, 48 hours
	Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/L, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Review federal, state/provincial, and local government requirements prior to disposal. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1170
Proper shipping name	Ethanol solutions
Hazard class	3
Subsidiary hazard class	Limited Quantity - US
Packing group	II
Special provisions	24, IB2, T4, TP1
Packaging exceptions	<0.3 Gallons - Limited Quantity
Packaging non bulk	202
Packaging bulk	242

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1170
Proper shipping name	ETHANOL SOLUTION with more than 24% ethanol, by volume
Hazard class	3

Subsidiary hazard class Limited Quantity - Canada
Packing group II
Special provisions 150
Packaging exceptions <1L - Limited Quantity

DOT



TDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Ethanol (CAS 64-17-5)	1 TONNES
Methanol (CAS 67-56-1)	1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1)	Listed.
Potassium hydroxide (CAS 1310-58-3)	Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Immediate Hazard - Yes
- Delayed Hazard - Yes
- Fire Hazard - Yes
- Pressure Hazard - No
- Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	1-5*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA) Hazardous substance

Section 112(r) (40 CFR 68.130)

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Ethanol (CAS 64-17-5) Listed.

Methanol (CAS 67-56-1) Listed.

Potassium hydroxide (CAS 1310-58-3) Listed.

US - Illinois Chemical Safety Act: Listed substance

Ethanol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Potassium hydroxide (CAS 1310-58-3)

US - Louisiana Spill Reporting: Listed substance

Ethanol (CAS 64-17-5) Listed.

Methanol (CAS 67-56-1) Listed.

Potassium hydroxide (CAS 1310-58-3) Listed.

US - Minnesota Haz Subs: Listed substance

Ethanol (CAS 64-17-5) Listed.

Methanol (CAS 67-56-1) Listed.

Potassium hydroxide (CAS 1310-58-3) Listed.

US - New Jersey RTK - Substances: Listed substance

Ethanol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Potassium hydroxide (CAS 1310-58-3)

US - Texas Effects Screening Levels: Listed substance

Ethanol (CAS 64-17-5) Listed.

Methanol (CAS 67-56-1) Listed.

Potassium hydroxide (CAS 1310-58-3) Listed.

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Potassium hydroxide (CAS 1310-58-3)

US. New Jersey Worker and Community Right-to-Know Act

Methanol (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Potassium hydroxide (CAS 1310-58-3)

US. Rhode Island RTK

Ethanol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Potassium hydroxide (CAS 1310-58-3)

US. California Proposition 65

Ethanol is only considered a Proposition 65 cancer and developmental hazard when it is ingested as an alcoholic beverage.

⚠ WARNING: This product can expose you to chemicals including Phenolphthalein, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Phenolphthalein (CAS 77-09-8) Listed: May 15, 1998

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The data contained in this material safety data sheet was obtained from sources that were technically accurate, reliable, and state of the art when this document was prepared. If data was unavailable to complete certain sections, the absence of that data is identified in this document. Because the supplier cannot know the exact circumstances during actual use of this product, other hazards, exposure scenarios, disposal considerations, and regulations may apply and it is the responsibility of the user to read and understand the product label and this document before use. Do not use the product for purposes other than those stated in Section 1.

Issue date

29-May-2018

Version

01

Effective date

29-May-2018

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.